

RECEIVED
CENTRAL FAX CENTER
APR 06 2009

Amendment to the Claims

1-3. (Cancelled)

4. (Currently Amended) ~~The device for supplying snap rings as set forth in Claim 1, further comprising~~ A device for supplying snap rings, the device comprising:

a magazine for containing C-shaped snap rings piled together, each of the snap rings being held in the magazine such that the gap is directed forward in a conveying direction;

a conveying base having a conveying path on a surface thereof, the magazine being provided on the conveying base;

an extrusion member that pushes out a snap ring occupying a lowest position in the magazine forward in the conveying direction along the conveying path;

an oscillating member that is protractible and retractable with respect to a conveying surface of the conveying path an area in front of the magazine in the conveying direction, the oscillating member being capable of entering the gap of the snap ring being pushed out so as to direct the gap forward in the conveying direction;

a projection-strip guide wall that is defined between a pair of concave parts extending in the conveying direction in a termination area of the conveying path of the conveying base, the projection-strip guide wall being formed so as to stand upwardly in the substantially vertical direction, wherein the projection-strip guide wall has a width that permits the projection-strip guide wall to enter the gap of the snap ring; and

a cover member provided on the conveying base in the termination area of the conveying path so as to cover the pair of concave parts and the projection-strip guide wall from above,

wherein:

the cover member has a pair of guide parts formed so as to protrude downwardly at positions whereat the pair of guide parts opposes the pair of concave parts; and

each of the pair of guide parts has a contact surface that is curved so that a projection amount thereof increases toward a front in the conveying direction.

5. (Currently Amended) The device for supplying snap rings as set forth in ~~Claim 1~~ Claim 4, wherein each bottom of the pair of concave parts is formed so as to define an inclined surface that descends toward a front in the conveying direction and is upwardly-convexly curved.

6-9. (Cancelled)

10. (Currently Amended) A device for supplying snap rings, the device comprising:
_____ a magazine for containing C-shaped snap rings piled together, each of the snap rings being held in the magazine such that the gap is directed forward in a conveying direction;
_____ a conveying base having a conveying path on a surface thereof, the magazine being provided on the conveying base;
_____ an extrusion member that pushes out a snap ring occupying a lowest position in the magazine forward in the conveying direction along the conveying path;
_____ an oscillating member that is protractible and retractable with respect to a conveying surface of the conveying path at an area in front of the magazine in the conveying direction, the oscillating member being capable of entering the gap of the snap ring being pushed out so as to

direct the gap forward in the conveying direction:

a projection-strip guide wall that is defined between a pair of concave parts extending in the conveying direction in a termination area of the conveying path of the conveying base, the projection-strip guide wall being formed so as to stand upwardly in a substantially vertical direction, wherein the projection-strip guide wall has a width that permits the projection-strip guide wall to enter the gap of the snap ring, wherein the oscillating member has an elongated guide part having a width that can enter the gap of the snap ring; and
an urging member for urging the oscillating member so that the guide part protrudes from the conveying surface.

~~The device for supplying snap rings as set forth in Claim 2,~~ wherein an end of the oscillating member is pivotally supported on the conveying base below the conveying surface.

11. (Currently Amended) The device for supplying snap rings as set forth in ~~Claim 1~~Claim 10, further comprising a rod and a spring for urging the oscillating member upwardly so that the oscillating member protrudes from the conveying surface.